B-LIFT 1000 HR

WORKING DIAGRAM



INFO

OUTRIGGERS
HE+HE

WORKING HEIGHT
99,50 m

BASKET HEIGHT
97,50 m

MAX OUTREACH
40,50 m (350 kg)

BASKET LOAD CAPACITY
600 kg

BASKET SIZE
2300/3600x900x1100 mm

BASKET ROTATION
180°+180°

CONTROLS
Electric

TURRET ROTATION
700°

GVW
53 ton



DIMENSIONS
STABILISERS
WITH MAX AREA



SCANIA P500

STANDARD ACCESSORIES

- Convertible basket possibility (Eternit)
- 2nd Jib 180 ° manual rotation
- Possibility of winch on removable JIB
- Automatic stabilization
- Partially stabilized working areas
- Automatic closing
- Basket control station with console on design including joystick and 7 “LCD display with real-time information
- Intercom with headphones for basket-ground communication
- Main and auxiliary motor start/stop control from the basket
- Multifunction radio remote control for emergency control of the aerial part from the ground and stabilization
- 2 fixed roto-lamp on the vehicle cabin
- Socket 230V/400V
- Heat exchanger on the hydraulic system
- 2 folding sides, 2 fixed (h 150 mm)
- 4 outrigger plates
- Anti-corrosion treatment on unpainted components

SAFETY DATA

- Emergency button
- Emergency manual hand pump
- Automatic PTO deactivation
- Cross-check of open stabilizers
- Anemometer
- Load limiter in the basket
- Moment limiter with double safety and control of correct operation
- Multi axial device for visual control of frame stabilization
- Emergency descent with electric pump (in the absence of the auxiliary motor)
- Rotation brake of the turret with automatic insertion
- Hydraulic system with differentiated filtering with high efficiency filters both on the delivery lines and on the return lines
- Multifunction radio control for emergency control
- Automatism for rotation lock with extension of the stabilizers on one side only
- Chassis flatness sensor
- Flanged block valves

CTE

ctelift.com